

## Technical info Storeroom walls

<b>Product info material StoreRoom walls</b>		
Product	Dimensions (mm)	Additional information
<b>F</b>		
Panel (frame)	Verticals 19,0 x 19,0 x 1,0	
	Horizontals 15,0 x 15,0 x 1,0	
Wire	Verticals $\varnothing$ 3,0	
	Horizontals $\varnothing$ 2,5	
	Mesh Apertures 48 x 62,5	
Door (frame)	Verticals 30,0 x 20,0 x 1,25	
	Horizontals 25,0 x 15,0 x 1,0	
Colour	RAL9018	
<b>FK</b>		
Panel (frame)	Verticals 30,0 x 20,0 x 1,25	
	Horizontals 25,0 x 15,0 x 1,0	
Wire	Verticals $\varnothing$ 5,0	
	Horizontals $\varnothing$ 4,0	
	Mesh Apertures 45 x 61	
Door (frame)	Verticals 40,0 x 20,0 x 1,5	
	Horizontals 35,0 x 15,0 x 1,5	
Colour	RAL9018	
<b>FK+</b>		
Panel (frame)	Verticals 30,0 x 20,0 x 1,25	Strengthened
	Horizontals 25,0 x 15,0 x 1,25	
Wire	Verticals $\varnothing$ 5,0	
	Horizontals $\varnothing$ 5,0	
	Mesh Apertures 50 x 65	
Door (frame)	Verticals 40,0 x 20,0 x 1,5	Strengthened
	Horizontals 35,0 x 15,0 x 1,5	
Colour	RAL9018	
<b>FP</b>		
Panel (Profiled Sheet Metal)	Deep of profile 30,0	
	Thickness of sheet 0,7	
Colour	Sendzimir	
Door (Sheet Metal)	Verticals 40,0 x 20,0 x 1,5	
	Horizontals 35,0 x 15,0 x 1,5	
	Thickness of sheet 1,25 - 50-70914	
Colour	RAL9018	
Lower attach for panel		U-Profile
		(F=19 x 19; FK/ FP=30 x 20)
Upper mount for panel		Ceiling fitting
		Sheet Metal 2 mm
Shelves		Made by blockboard (Birch/Al)
		Brackets included



## Technical info Storeroom walls

**Cleaning:** To clean use water and a light detergent and rinse off with lukewarm water. The excess water can be dried with a lint-free cotton cloth. Abrasives, wire brush, scouring pad, or other products with abrasive effects may not be used. Avoid drying with paper that easily scratches.

OPERATING AND MAINTENANCE INSTRUCTIONS					
CLEANING	PERFORMED X NUMBER OF TIMES A			IN CASE	ANNEX
	WEEK	MONTH	YEAR		
				X	

Improvement of colour can be made if necessary. Extra spray paint can be purchased from Axelent AB.

Warranty: 2 years.

NOTE! Axelent mesh, plastic and sheet steel panels must not be stored outdoors or in humid conditions where the risk of rust is.

### ▶ CONTACT INFO

Axelent AB, Box 1, SE-330 33 Hillerstorp  
+46 (0)370-37 37 36, teambygg@axelent.se  
www.axelent.com